RoHS

SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Insulator Material:Polyester(UL94V−0)
Resistance To Soldering Heat:
260° C±5° C, 10s(PA6T&PA9T&LCP insulator)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)



Ordering Information

1430 11 XX X W XX Z XXX X 0 X

- No.of Pins Per Row 11P
- Insulator Material Option
  - C=BK−PA6T
  - E=BK−PA9T
  - F=BK−LCP
- Contact Plating
  - G0:Gold Flash
  - G1:1u" Gold
  - G2:1.5u" Gold
  - G3:2u" Gold
  - G4:3u" Gold
  - G5:5u" Gold
  - G6:10u" Gold
  - G7:15u" Gold
  - G8:30u" Gold
  - S0:Gold Flash/Tin
  - SN:Tin
- Pin Length
- Packing
  - A=Tray
  - T=Tube
  - P=Tube+Cap
  - R=Reel+Cap
  - M=Reel+Mylar





Dimension antitheses list			
ITEM	PA	A	PC
Standard	XXX	XXX	XXX

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS

UNSPECIFIED TOLERANCES	
ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

www.hiemi.cn

HIEMI TECHNOLOGY CO., LTD

DSND		SCALE: N/A	
DWN		VIEW:	PART NO.: 430 XXXWXXZXXXX0X
CHKD		UNIT: mm/in	DWG NO.: 1.27PH H3.0mm 1xNpin 90° SMT
APPD		SIZE: A4	

WEIGHT	SHEET	REVISION
	1/1	A0