

RoHS


SPECIFICATIONS
Rated Current:1.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c


Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Resistance To Soldering Heat:
245° C±5° C, 10s(PBT insulator)
260° C±5° C, 10s(PA6T&PA9T&LCP insulator)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)







Ordering Information

14XX 2 2 XX X N XX R XXX X 0X

- **14XX** — High.of Plastic: 10=H1.0mm, 15=H1.5mm, 16=H1.6mm, 20=H2.0mm, 25=H2.5mm, 30=H3.0mm
- **22** — Fixed
- **XX** — No.of Pins Per Row: 02~50P
- **X** — Insulator Material Option: A=BK−PBT, C=BK−PA6T, E=BK−PA9T, F=BK−LCP
- **N** — Fixed
- **XX** — Contact Plating: G0:Gold Flash, G1:1u" Gold, G2:1.5u" Gold, G3:2u" Gold, G4:3u" Gold, G5:5u" Gold, G6:10u" Gold, G7:15u" Gold, G8:30u" Gold, S0:Gold Flash/Tin, SN:Tin
- **R** — Fixed
- **XXX** — Pin Length
- **X** — Packing: 0=PE Bag, A=Tray, T=Tube, P=Tube+Cap, R=Reel+Cap, M=Reel+Mylar
- **0X** — Fixed

Dimension antitheses list						
H	1.0	1.5	1.6	2.0	2.5	3.0
W	3.4	3.4	3.0	3.0	3.0/3.4	3.4

Dimension antitheses list				
ITEM	PA	PB	PC	D
Alternate	XXX	XXX	XXX	XXX

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS

UNSPECIFIED TOLERANCES	
ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

www.hiemi.cn

HIEMI TECHNOLOGY CO., LTD

DSND		SCALE: N/A	
DWN		VIEW:	PART NO.: 14XX22XXXNXXRXXXX0X
CHKD		UNIT: mm/in	DWG NO.: 1.27mm Pin Header 90°
APPD		SIZE: A4	

WEIGHT	SHEET	REVISION
	1/1	A0