

RoHS

SPECIFICATIONS
Rated Current:2.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Resistance To Soldering Heat:
245° C±5° C, 10s(PBT insulator)
260° C±5° C, 10s(PA6T&PA9T&LCP insulator)




Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)




Ordering Information

13XX 1 1 XX X N XX R XXX X 0X

High.of Plastic	No.of Pins Per Row	Insulator Material Option	Contact Plating			Pin Length	Packing
10=H1.0mm	02~40P	A=BK−PBT	G0:Gold Flash	G5:5u" Gold	SO:Gold Flash/Tin		0=PE Bag
15=H1.5mm		C=BK−PA6T	G1:1u" Gold	G6:10u" Gold	SN:Tin		A=Tray
20=H2.0mm		E=BK−PA9T	G2:1.5u" Gold	G7:15u" Gold			T=Tube
25=H2.5mm		F=BK−LCP	G3:2u" Gold	G8:30u" Gold			P=Tube+Cap
30=H3.0mm			G4:3u" Gold				R=Reel+Cap
40=H4.0mm							M=Reel+Mylar





Dimension antitheses list			
ITEM	PA	PB	PC
Alternate	XXX	XXX	XXX

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS

UNSPECIFIED TOLERANCES	
ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

www.hiemi.cn

HIEMI TECHNOLOGY CO., LTD

DSND		SCALE: N/A
DWN		VIEW:
CHKD		UNIT: mm/in
APPD		SIZE: A4

PART NO.: 13XX11XXXNXXRXXXX0X
DWG NO.: 2.0mm Pin Header 90°正弯

WEIGHT	SHEET	REVISION
	1/1	A0