RoHS

SPECIFICATIONS
Rated Current:2.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:500V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Resistance To Soldering Heat:
245° C±5° C, 10s(PBT insulator)
260° C±5° C, 10s(PA6T&PA9T&LCP insulator)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)



Ordering Information

1340 1 2 XX X N XX S XXX X 0X

- 1340: High.of Plastic 40=H4.0mm
- 1 2: No.of Pins Per Row 02~40P
- XX: Insulator Material Option
  A=BK−PBT
  C=BK−PA6T
  E=BK−PA9T
  F=BK−LCP
- X: N
- XX: Contact Plating
  G0:Gold Flash
  G1:1u" Gold
  G2:1.5u" Gold
  G3:2u" Gold
  G4:3u" Gold
  G5:5u" Gold
  G6:10u" Gold
  G7:15u" Gold
  G8:30u" Gold
  S0:Gold Flash/Tin
  SN:Tin
- S: Pin Length
- XXX: Packing
  0=PE Bag
  A=Tray
  T=Tube
  P=Tube+Cap
  R=Reel+Cap
  M=Reel+Mylar
- X: 0X





Dimension antitheses list		
ITEM	PA	PC
Alternate	XXX	XXX

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS

UNSPECIFIED TOLERANCES	
ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

www.hiemi.cn

HIEMI TECHNOLOGY CO., LTD

DSND		SCALE: N/A
DWN		VIEW:
CHKD		UNIT: mm/in
APPD		SIZE: A4

PART NO.: 134012XXXNXXSXXXX0X
DWG NO.: 2.0mm Pin Header 180°

WEIGHT	SHEET	REVISION
	1/1	A0