RoHS

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Resistance To Soldering Heat:
245° C±5° C, 10s(PBT insulator)
260° C±5° C, 10s(PA6T&PA9T&LCP insulator)



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)



Ordering Information

12XX 1 2 XX X N XX R XXX X 0X

- 12XX: High.of Plastic — 10=H1.0mm, 15=H1.5mm, 17=H1.7mm, 20=H2.0mm, 25=H2.5mm, 30=H3.0mm, 43=H4.3mm
- 1 2: No.of Pins Per Row — 02~40P
- XX: Insulator Material Option — A=BK−PBT, C=BK−PA6T, E=BK−PA9T, F=BK−LCP
- X: Contact Plating — G0:Gold Flash, G1:1u" Gold, G2:1.5u" Gold, G3:2u" Gold, G4:3u" Gold, G5:5u" Gold, G6:10u" Gold, G7:15u" Gold, G8:30u" Gold, S0:Gold Flash/Tin, SN:Tin
- N: Pin Length
- XX: Packing — 0=PE Bag, A=Tray, T=Tube, P=Tube+Cap, R=Reel+Cap, M=Reel+Mylar
- R: Packing
- XXX: Packing
- X: Packing
- 0X: Packing





Dimension antitheses list			
ITEM	PA	PB	PC
Alternate	XXX	XXX	XXX

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS

ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

UNSPECIFIED TOLERANCES

www.hiemi.cn

HIEMI TECHNOLOGY CO., LTD

DSND		SCALE: N/A	
DWN		VIEW:	PART NO.: 12XX12XXXNXXRXXXX0X
CHKD		UNIT: mm/in	DWG NO.: 2.54mm Pin Header 90°正弯
APPD		SIZE: A4	WEIGHT / SHEET 1/1 / REVISION A0