RoHS

SPECIFICATIONS
Rated Current:3.0AMP
Contact Resistance:20mΩ Max
Withstand Voltage:1000V AC/DC
Insulation Resistance:1000MΩ Min
Operation Temperature:−40°c to +105°c

Contact Material:Brass
Contact Plating:Au Over Ni
Insulator Material:Polyester(UL94V−0)
Resistance To Soldering Heat:
260° C±5° C, 10s(PA6T&PA9T&LCP insulator)







Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE± 0.05)







Dimension antitheses list				
ITEM	PA	PB	D	W
Alternate	XXX	XXX	XXX	XXX

Ordering Information

12XX 2 1 XX X N XX M XXX X 0X

- 12XX: High.of Plastic — 10=H1.0mm, 15=H1.5mm, 17=H1.7mm, 20=H2.0mm, 25=H2.5mm, 30=H3.0mm, 33=H3.3mm
- 21: No.of Pins Per Row — 02~40P
- XX: Insulator Material Option — C=BK−PA6T, E=BK−PA9T, F=BK−LCP
- N: Contact Plating — G0:Gold Flash, G1:1u" Gold, G2:1.5u" Gold, G3:2u" Gold, G4:3u" Gold, G5:5u" Gold, G6:10u" Gold, G7:15u" Gold, G8:30u" Gold, S0:Gold Flash/Tin, SN:Tin
- M: Pin Length
- XXX: Packing — 0=PE Bag, A=Tray, T=Tube, P=Tube+Cap, R=Reel+Cap, M=Reel+Mylar
- X: 0X

MARK	DESCRIPTION	DATE	REVISED	APPROVED
ΔX				
ΔX				
ΔX				

REVISIONS

ANGLAR	±5°
L≤ 4	±0.2
4<L≤ 16	±0.3
16<L≤ 63	±0.4
L> 63	±0.5

UNSPECIFIED TOLERANCES

www.hiemi.cn

HIEMI TECHNOLOGY CO., LTD

DSND		SCALE: N/A
DWN		VIEW:
CHKD		UNIT: mm/in
APPD		SIZE: A4

PART NO.: 12XX21XXXNXXMXXXX0X
DWG NO.: 2.54mm Pin Header SMT

WEIGHT	SHEET	REVISION
	1/1	A0